

MID-LEVEL INFRARED DRYERS

LITTLERed X1

**15 YEAR
HEATER WARRANTY**

All LittleRed series dryers have a tilting heater design. Works great for curing hats!!



LR-X1-30
120V available



LR-X1-54

CE CERTIFIED
BY CERTIFICATION EXPERTS
THE NETHERLANDS

Single Infrared Element

LR-X1-30

2,600w @240V
2,000w @120V

30" (76cm)

24" (61cm)

48" (122cm)

18" (46cm)

177 CFM (5 CMM)

130+/hr (240v) - 90+/hr (120v)

45+/hr (240v or 120v)

Single Infrared Element

LR-X1-54

5,200w @240V

54" (137.2cm)

48" (122cm)

66" (168cm)

18" (46cm)

388 CFM (11 CMM)

260+/hr

90+/hr

Total Wattage

Belt Width

Heater Width**

Conveyor Length

Chamber Length

Powered Exhaust

Cure Times: Plastisol @ 25 secs.*

Waterbased/Discharge @ 70 secs.*

Features

- HEAVY DUTY** "X-Series" Conveyor Belt Roller Tracking System with 30" (76 cm) or 54" (137 cm) wide Teflon coated fiberglass belt
- ACCURATE** Digital PID Temperature controller is accurate to +/-1°F
- ADJUSTABLE** 2" - 7" (5 - 17.7 cm) belt-to-heater clearance, adjustable separately on each side for each heater
- EXHAUST** Powered exhaust to remove fumes and moisture
- CONSISTENT** DC belt speed control w/ digital display
- EXPANDABLE** Add 18" (46cm) and 36" (92 cm) chambers and/or 18" (46 cm) belt extensions

Options

- Additional chambers can be added as well as belt extensions
- Heavy duty belt motor
- Locking casters for easy mobility
- Chambers can be purchased separately to add onto any LittleRed, EconoRed and BigRed dryer
- UL and ULc Certified

* Production speeds are estimates are based on 16" centers and will vary depending on ink manufacturer, humidity of shop, and other variables.

** Recommended maximum image width = heater width minus 4" (10cm).



MID-LEVEL INFRARED DRYERS

LITTLERed SERIES

**15 YEAR
HEATER WARRANTY**



LR-X2-30



LR-X2-54



LR-X3-30



LR-X3-54

All LittleRed series dryers have a tilting heater design. Works great for curing hats!!



| | Dual Infrared Elements LR-X2-30 | Dual Infrared Elements LR-X2-54 | Three Infrared Elements LR-X3-30 | Three Infrared Elements LR-X3-54 |
|--|---|---|--|--|
| Total Wattage | 5,200w @240V | 10,400w @240V | 7,800w @240V | 15,600w @240V |
| Belt Width | 30" (76cm) | 54" (137.2cm) | 30" (76cm) | 54" (137.2cm) |
| Heater Width** | 24" (61cm) | 48" (122cm) | 24" (61cm) | 48" (122cm) |
| Conveyor Length | 66" (1.68m) | 66" (1.68m) | 88" (2.24m) | 88" (2.24m) |
| Chamber Length | 27" (69cm) | 27" (69cm) | 41" (104cm) | 41" (104cm) |
| Powered Exhaust | 300 CFM (8.5 CMM) | 350 CFM (9.9 CMM) | 388 CFM (11 CMM) | 550 CFM (15.6 CMM) |
| Cure Times: Plastisol @ 25 secs.* | 260+/hr | 520+/hr | 360+/hr | 720+/hr |
| Waterbased/Discharge @ 70 secs.* | 90+/hr | 180+/hr | 120+/hr | 240+/hr |

Features

- HEAVY DUTY** "X-Series" Conveyor Belt Roller Tracking System with 30" (76 cm) or 54" (137 cm) wide Teflon coated fiberglass belt
- ACCURATE** Digital PID Temperature controller is accurate to +/-1°F
- ADJUSTABLE** 2" - 7" (5 - 17.7 cm) belt-to-heater clearance, adjustable separately on each side for each heater
- EXHAUST** Powered exhaust to remove fumes and moisture
- CONSISTENT** DC belt speed control w/ digital display
- EXPANDABLE** Add 18" (46cm) and 36" (92 cm) chambers and/or 18" (46 cm) belt extensions

Options

- Additional chambers can be added as well as belt extensions
- Heavy duty belt motor (Standard on X2-54)
- Locking casters for easy mobility
- UL and ULc Certified

* Production speeds are estimates are based on 16" centers and will vary depending on ink manufacturer, humidity of shop, and other variables.
** Recommended maximum image width = heater width minus 4" (10cm).




INFRARED DRYER ACCESSORIES




SI-27
Stand for D-100



**SI-27 W/
SI-27-DEMT**
Stand for D-1000




WS-EDD
Drop Down Wheel Set for
DB, LR & EC-I Dryers



WS-EC
Standard Wheel Set for
all non-tabletop Dryers

WS-EHD
Drop Down Wheel Set for
EC-II, ER & BR Dryers



EXHAUST HOOD

FEATURES


- Removes fumes at exit the dryer
- EXH-30 fits 30" (76cm) wide belts
- EXH-54 fits 54" (137cm) wide belts
- Available in 120v or 240v



CONVEYOR AIR BAR

FEATURES


- Cools ink as garments exit the dryer
- CAB-30 fits 30" (76cm) wide belts
- CAB-54 fits 54" (137cm) wide belts
- Work on many non-Vastex dryers
- Available in 120v or 240v



HAT SUPPORT RAIL

FEATURES

- Angles hats so front is parallel with heaters
- HR-1 fits EconoRed II dryers
- HR-2 fits EconoRed III & BigRed Dryers



CONVEYOR EXTENSIONS


Extend your conveyor in
18" (46cm), 36" (92cm) and
54" (137cm) increments



D-100, D-1000, & LittleRed Technical Specifications



| | D-100 | D-1000 | LR-X1-30 | LR-X2-30 | LR-X1-54 | LR-X2-54 | LR-X3-30 | LR-X3-54 |
|--|---|---|--|--|--|--|---|---|
| Heater Warranty | 15 Year | 15 Year | 15 Year | 15 Year | 15 Year | 15 Year | 15 Year | 15 Year |
| Defect Warranty | 3 Year | 3 Year | 3 Year | 3 Year | 3 Year | 3 Year | 3 Year | 3 Year |
| Shirts / Hr Plastisol | 110+@ 25 secs. | 110+@ 25 secs. | 90+(120V)/130+(240V) @ 25 secs. | 260+@ 25 secs. | 260+@ 25 secs. | 520+@ 25 secs. | 360+@ 25 secs. | 720+@ 25 secs. |
| Shirts/hr w/b/discharge | 50+@ 70 secs. | 50+@ 70 secs. | 45+@ 70 secs. | 90+@ 70 secs. | 90+@ 70 secs. | 180+@ 70 secs. | 120+@ 70 secs. | 240+@ 70 secs. |
| Time in Tunnel Range (mm:ss) | 00:17 - 01:20 | 00:17 - 01:20 | 00:17 - 01:46 | 00:14 - 01:28 | 00:17 - 01:46 | 00:11 - 01:39 | 00:11 - 01:35 | 00:11 - 01:35 |
| Belt Speed | 0.6 - 7.4 FPM (0.18 - 2.3 MPM) | 0.6 - 7.4 FPM (0.18 - 2.3 MPM) | 0.6 - 7.4 FPM (0.18 - 2.3 MPM) | 1.4 - 17.7 FPM (0.4 - 5.4 MPM) | 0.6 - 7.4 FPM (0.18 - 2.3 MPM) | 1.4 - 17.7 FPM (0.4 - 5.4 MPM) | 1.4 - 7.4 FPM (0.18 - 2.3 MPM) | 1.4 - 7.4 FPM (0.18 - 2.3 MPM) |
| Exhaust (Free Air) | n/a | n/a | 177 CFM (5 CMM) | 300 CFM (8.5 CMM) | 300 CFM (8.5 CMM) | 350 CFM (9.9 CMM) | 388 CFM (11 CMM) | 550 CFM (15.6 CMM) |
| Exhaust Diameter | n/a | n/a | 3" (7.62 cm) | 3" (7.62 cm) | 3" (7.62 cm) | 4" (10.16 cm) | 4" (10.16 cm) | 4" (10.16 cm) |
| Overall Length | 46" (117 cm) | 56" (143 cm) | 48" (122 cm) | 66" (168 cm) | 66" (168 cm) | 66" (168 cm) | 88" (224 cm) | 88" (224 cm) |
| Overall Width | 24" (61 cm) | 32" (81 cm) | 41" (105cm) | 41" (105 cm) | 65" (166 cm) | 65" (166 cm) | 41" (105 cm) | 65" (166 cm) |
| Overall Height | 24" (61 cm) | 24" (61 cm) | 48" (122cm) | 50" (127 cm) | 48" (122cm) | 50" (127 cm) | 50" (127 cm) | 50" (127 cm) |
| Belt Width | 18" (45.7 cm) | 26" (66 cm) | 30" (76 cm) | 30" (76 cm) | 54" (137cm) | 54" (137cm) | 30" (76cm) | 54" (137cm) |
| Chamber Length | 18" (45.7 cm) | 18" (45.7 cm) | 18" (46cm) | 27" (69cm) | 18" (46cm) | 27" (69cm) | 41"(104cm) | 41"(104cm) |
| Chamber Infeed Width | 19.5" (49.5 cm) | 27.75" (70.5 cm) | 33.5" (85cm) | 33.5" (85 cm) | 58.5" (149 cm) | 58.5" (149 cm) | 33.5" (85 cm) | 58.5" (149 cm) |
| Chamber Infeed Height(adjustable) | 2" - 7" (5 - 17.7 cm) | 2" - 7" (5 - 17.7 cm) | 2" - 7" (5 - 17.7 cm) | 2" - 7" (5 - 17.7 cm) | 2" - 7" (5 - 17.7 cm) | 2" - 7" (5 - 17.7 cm) | 2" - 7" (5 - 17.7 cm) | 2" - 7" (5 - 17.7 cm) |
| Heat Range (@ Heater) | 0-750 F° (0-399 C°) @ 120 or 240V | 0-750 F° (0-399 C°) @ 120 or 240V | 0-900F° (0-482C°) @ 240V 0-750F° (0-399C°) @ 120V | 0-900 F° (0-482 C°) @ 240V | 0-900 F° (0-482 C°) @ 240V | 0-900 F° (0-482 C°) @ 240V | 0-900 F° (0-482 C°) @ 240V | 0-900F° (0-482C°) @ 240V |
| Heater Size | 16"x16"(40.6x40.6 cm) | 16"x20"(40.6x50.8 cm) | 12" x 24" (30 x 61 cm) | 12" x 24" (30 x 61 cm) | 12" x 48" (30 x 122 cm) | 12" x 48" (30 x 122 cm) | 12" x 24" (30 x 61 cm) | 12" x 48" (30 x 122 cm) |
| Total Wattage | 1,625 Watts | 2,025 Watts | 240V / 1 @ 2,600 Watts 120V / 1 @ 2,000 Watts | 2,600 = 5,200 Watts | 5,200 Watts | 10,400 Watts @ 240V 12,000 Watts @ 380V | 7,800 Watts Total | 15,600 Watts Total |
| Cost/hr to operate based on 10 cents/kwh | 16 cents | 20 cents | 26 cents @ 240V 20 cents @ 120V | 52 cents | 52 cents | \$1.04 | 78 cents | 1.56 cents |
| Electrical Specs** Chamber | 120V / 12.5A / NEMA 5-15P 240V / 6.5A / 1 Ph. / NEMA 6-15P | 120V / 16.5A / NEMA 5-20P 240V / 8.2A / 1 Ph. / NEMA 6-15P | 240V / 11A / 1 Ph. / NEMA 6-15P 120V / 16.5A / NEMA 5-20P | 240V / 21.6A / 1 Ph. / 3 wire 50/60HZ | 240V / 22A / 1 Ph. / 3 wire 50/60HZ | 240V / 44A / 1 Ph. / 3 wire 50/60HZ | 240V / 34A / 1 Ph. / 3 wire 50/60HZ | 240V / 68A / 1 Ph. / 3 wire 50/60HZ |
| Electrical Connection | Cordset Included | Cordset Included | Cordset Included | All amps shown are FLA (Full Load Amps), not recommended line size! Dryers on this page must be hard wired to the power terminal provided. A licensed electrician must be consulted and should refer to articles, 210.20(a), 215.3 and 310 of the NEC code. | | | | |
| Optional Power | 208V / 6.5A / 1 Ph. / NEMA 6-15P | 208V / 8.2A / 1 Ph. / NEMA 6-15P | 208V / 11A / 1 Ph. / NEMA 6-15P | 208V / 21.6A / 1 Ph. / 3 wire 50/60HZ 240V / 15A / 3 Ph 5 wire 50/60HZ 380V / 9A / 3 Ph. / 5 wire 50/60HZ | 208V / 22A / 1 Ph. / 3 wire 50/60HZ 240V / 15A / 3 Ph 5 wire 50/60HZ 380V / 10A / 3 Ph. / 5 wire 50/60HZ | 208V / 44A / 1 Ph. / 3 wire 50/60HZ 240V / 28A / 3 Ph 5 wire 50/60HZ 380V / 20A / 3 Ph. / 5 wire 50/60HZ | 240V / 21A / 3 Ph 5 wire 50/60HZ 380V / 13A / 3 Ph. / 5 wire 50/60HZ | 240V / 40A / 3 Ph 5 wire 50/60HZ 380V / 26A / 3 Ph. / 5 wire 50/60HZ |
| Unit Weight | 89 lbs (41 kg) | 114 lbs (52 kg) | 172 lbs (78 kg) | 304 lbs (138 kg) | 380 lbs (173 kg) | 480 lbs (218 kg) | 424 lbs (193 kg) | Call for details |
| Shipping Weight** | Box 1 - 57 lbs (26 kg) Box 2 - 16 lbs (7.3 kg) Box 3 - 21 lbs (9.6 kg) Boxes on skid - 115 lbs (52 kg) | Box 1 - 17 lbs (7.7 kg) Box 2 - 24 lbs (10.9 kg) Box 3 - 35 lbs (15.9 kg) Box 4 - 43 lbs (19.5 kg) Box 5 - 11 lbs (5 kg) Boxes on Skid - 226 lbs (105.5 kg) | 300 lbs (136 kg) | 495 lbs (225 kg) | 550 lbs (250 kg) | 638 lbs (290 kg) | 548 lbs (249 kg) | 828 lbs (376 kg) |
| Shipping Dimensions** | Box #1 - 51.5x25x8" (131x64x20 cm) Box #2 - 21x21x7" (53x53x18 cm) Box #3 - 25x18x6" (64x46x15 cm) On Skid - 52x26x22" (132x96x51cm) | Box #1 - 27x21x7" (69x54x18 cm) Box #2 - 31x21x9" (79x54x23 cm) Box #3 - 36x31x8" (92x79x21 cm) Box #4 - 36x31x8" (92x79x21 cm) Box #5 - 31x15x8" (79x38x21 cm) On Skid - 49"x37"x26" (125x94x66 cm) | 25" x 48" x 35" (64 x 122 x 89 cm) | 50" x 48" x 40" (127 x 122 x 102 cm) | 70" x 42" x 58" (178 x 107 x 148 cm) | 70" x 42" x 58" (178 x 107 x 148 cm) | 49" x 45" x 56" (125 x 115 x 143 cm) | 69" x 49" x 58" (176 x 125 x 148 cm) |



1 in = 2.54 cm
1 lb = 0.454 kg

LR_D-SERIES_0421

* Production speeds are estimates are based on 16" centers and will vary depending on ink manufacturer, humidity of shop, and other variables.

**All shipping weights and dimensions are for continental US shipping only. Call for other shipping specifications. Ex-works from Bethlehem, PA.